MULE™ 4000







POWER

Engine 4-stroke, 2-cylinder, OHV 90° V Liquid-cooled

Displacement 617cc

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Maximum Torque 34.7 lb-ft @ 2500 rpm

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with differential

lock

Engine Braking No

Alternator Output 23 amp

(max)

Ground Clearance 7.5 in

Fuel Capacity 6.3 gal

Turning Radius 11.0 ft

Cargo Bed

Dimensions (LxWxH)

46.3 x 51.6 x 11.4 in

Cargo Bed Capacity 800 lb
Load Capacity 1327 lb

Seating Capacity

DETAILS

Overall Length

Overall Width

Overall Height

Curb Weight

Wheelbase

Instruments

Towing Capacity 1200 ll

Lighting (2) Halogen headlights (2) tail/brake lights

116.7 in

62.0 in

75.8 in

73.6 in

1338.4 lb*

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

tear Suspension / DeDion Axle/2.8 in

Rear Suspension / Wheel Travel

Debion / Me/ 2.0 1

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Park Brake Type Independent, Mechanical Drum

Steering Rack-and-pinion

Front Brakes Drum

Wheel Type
Color Choices

Dark Royal Red

Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

Warranty 1 Year

arranty



Rear Brakes



Drum

