MULE PRO-FXT™







POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

812cc Displacement

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Maximum Torque 48.0 lb-ft @ 3500 rpm

Fuel System DFI® with 34mm throttle body

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive**

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

Ground Clearance 10.2 in **Fuel Capacity** 7.9 gal

Turning Radius 16.0 ft

Cargo Bed "42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6-**Dimensions (LxWxH)**

person)"

999 lb (3-person), 350 lb (6-person), (348 lb for California **Cargo Bed Capacity**

models)

Load Capacity 1616.3 lb (1263.5 for California models)

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2000 lb

Lighting (2) Halogen headlights

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone / 8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires

26x9.00-12, radial

Rear Tires

Steering

Independent, Mechanical Disc

Park Brake Type

Rack-and-pinion

26x11.00-12, radial

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

DETAILS

Overall Length

133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1887.5 lb*

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning

indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps

Wheel Type Steel

Color Choices Super Black

Warranty 1 Year

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471