MULE PRO-FXT™ EPS









POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

812cc Displacement

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Maximum Torque 48.0 lb-ft @ 3500 rpm

DFI® with 34mm throttle body **Fuel System**

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

CAPABILITY

(max)

75 amp

Double wishbone/8.7 in

Wheel Travel

Front Suspension /

Rear Suspension /

Wheel Travel

Park Brake Type

Double wishbone/8.5 (L) /8.7 (R) in

Independent, Mechanical Disc

26x9.00-12, radial

Front Tires

Rear Tires 26x11.00-12, radial

Electric Power Steering (EPS), Tilt steering Steering

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

Ground Clearance 10.2 in

7.9 gal **Fuel Capacity**

Turning Radius 16.0 ft

42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6-Cargo Bed **Dimensions (LxWxH)**

Cargo Bed Capacity 999 lb (3-person), 350 lb (6-person), (348 lb for California

models)

Load Capacity 1616.3 lb (1263.5 for California models)

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2000 lb

Lighting (2) Halogen headlights

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1911.7 lb*

Wheelbase 92.3 in

Multi-function display includes digital speedometer, fuel Instruments

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Wheel Type Steel

Color Choices Timberline Green, Bright White

Warranty 1 Year

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.