2023 **MULE PRO-FXT[™] RANCH EDITION**





METALLIC TITANIUM



POWER

		Fuel Capa	
Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas	Turning Ra	
Displacement	812cc	Cargo Bed Dimension	
Bore x Stroke	2.83x2.62 in		
Compression Ratio	9.5:1	Cargo Bed	
Maximum Torque	48.0 lb-ft @ 3500 rpm		
Fuel System	DFI® with 34mm throttle body	Load Capa	
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Seating Ca	
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Towing Ca Lighting	
Engine Braking	Yes	DETAI	
Alternator Output	75 amp	DETAI	
(max)		Overall Le	

Ground Clearance	10.0 in	
Fuel Capacity	7.9 gal	
Turning Radius	16.0 ft	
Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6-person)	
Cargo Bed Capacity	999 lb (3-person), 350 lb (6-person), (348 lb for California models)	
Load Capacity	1616.3 lb (1263.5 for California models)	
Seating Capacity	3-person (1 row), 6 person (2 row)	
Towing Capacity	2000 lb	
Lighting	(2) Halogen headlights. (2) LED headlights	

ILS

75 amp			
	Overall Length	135.6 in	
	Overall Width	64.0 in	
	Overall Height	79.5 in	
Double wishbone/8.7 in	Curb Weight	1971.3 lb*	
Double wishbone/8.5 (L) /8.7 (R) in	Wheelbase	92.3 in	
26x9.00-12, radial 26x11.00-12, radial Independent, Mechanical Disc	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps	
Electric Power Steering (EPS), Tilt steering	Wheel Type	Alloy	
Dual Disc, 2 piston caliper	Color Choices	Metallic Titanium	
Dual Disc, 1 piston caliper	Warranty	1 Year	

Scan with camera to view videos, key features and more.

CAPABILITY

Front Suspension /

Wheel Travel Rear Suspension /

Wheel Travel **Front Tires**

Rear Tires

Steering **Front Brakes**

Rear Brakes

Park Brake Type



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULETM PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

WARN®? VRX 45, the WARN logo and THE RED HOOK STRAP are registered trademarks of Warn Industries, Inc.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULETM side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2022 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.