2023 MULE PRO-FXTTM RANCH EDITION PLATINUM^{Kawasaki}



METALLIC RUSTIC BRONZE



POWER

		Fuel Capacit
Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas	Turning Rad
Displacement	812cc	Cargo Bed
Bore x Stroke	2.83x2.62 in	Dimensions
Compression Ratio	9.5:1	Cargo Bed C
Maximum Torque	48.0 lb-ft @ 3500 rpm	Load Capaci
Fuel System	DFI® with 34mm throttle body	Seating Cap
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Towing Cap
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with	
	differential lock	Lighting
Engine Braking	Yes	DETAIL
Alternator Output	75 amp	
(max)		Overall Len

Ground Clearance	10.0 in	
Fuel Capacity	7.9 gal	
Turning Radius	16.0 ft	
Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6-person)	
Cargo Bed Capacity	999 lb (3-person), 350 lb (6-person), (348 lb for California models)	
Load Capacity	1616.3 lb (1263.5 for California models)	
Seating Capacity	3-person (1 row), 6 person (2 row)	
Towing Capacity	2000 lb	
Lighting	(4) LED headlights	

S

	-		
	Overall Length	140.2 in	
	Overall Width	64.0 in	
	Overall Height	79.5 in	
n	Curb Weight	2035.2 lb*	
L) /8.7 (R) in	Wheelbase	92.3 in	
cal Disc	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps	
g (EPS), Tilt steering	Wheel Type	Alloy	
per	Color Choices	Metallic Rustic Bronze	
per	Warranty	1 Year	

Scan with camera to view videos, key features and more.

CAPABILITY

Front Suspension /

Wheel Travel Rear Suspension /

Wheel Travel **Front Tires**

Rear Tires

Steering

Front Brakes

Rear Brakes

Park Brake Type



Double wishbone/8.7 in

Double wishbone/8.5 (L

Independent, Mechanica

Electric Power Steering

Dual Disc, 2 piston calip

Dual Disc, 1 piston calip

26x9.00-12, radial

26x11.00-12, radial

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULETM PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

WARN®? VRX 45, the WARN logo and THE RED HOOK STRAP are registered trademarks of Warn Industries, Inc.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2022 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.