## **MULE PRO-MX™ EPS**









## **POWER**

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Bore x Stroke 102.0 x 85.0 mm

Compression Ratio 10.3:1

Maximum Torque 42.7 lb-ft @ 5000 rpm

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with centrifugal

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft, Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

35.7 amp

## **CAPABILITY**

Front Suspension /

Wheel Travel

Double wishbone/8.6 in

Rear Suspension / Wheel Travel Double wishbone/9.1 in

Front Tires

25x8.00-12, radial

Rear Tires

25x10.00-12, radial

Park Brake Type

Independent, Mechanical Disc

Steering

Electric Power Steering (EPS), Tilt steering

**Front Brakes** 

Dual Disc, 2 piston caliper

**Rear Brakes** 

Dual Disc, 1 piston caliper

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Cargo Bed

Dimensions (LxWxH)

**Turning Radius** 

Cargo Bed Capacity 699 lb (600 lb California models)

14.0 ft

Load Capacity 1200 lb

Seating Capacity

Towing Capacity 1500 lb

Lighting (2) Halogen headlights. (2) LED headlights

33.4 x 44.1 x 9.1 in

## **DETAILS**

Overall Length 110.0 in
Overall Width 60.0 in

Overall Height 74.4 in

Curb Weight 1587.6 lb\*

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

lamps

Wheel Type Steel

Color Choices Timberline Green, Firecracker Red

Warranty 1 Year

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.