MULE PRO-MX™ EPS LE







POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

695cc Displacement

Bore x Stroke 102.0 x 85.0 mm

Compression Ratio 10.3:1

Maximum Torque 42.7 lb-ft @ 5000 rpm

DFI® with 44mm throttle body **Fuel System**

Continuously Variable Transmission (CVT) with centrifugal **Transmission**

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft, Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 35.7 amp

(max)

Fuel Capacity

Ground Clearance

Turning Radius

9.5 gal

Cargo Bed Dimensions (LxWxH)

Cargo Bed Capacity 699 lb (600 lb California models)

10.6 in

14.0 ft

Load Capacity 1200 lb

Seating Capacity

1500 lb **Towing Capacity**

Lighting (2) Halogen headlights. (2) LED headlights

33.4 x 44.1 x 9.1 in

CAPABILITY

Double wishbone/8.6 in Front Suspension / Wheel Travel

Rear Suspension /

Double wishbone/9.1 in

Wheel Travel Front Tires 25x10.00-12, radial

Rear Tires

25x10.00-12, radial Independent, Mechanical Disc

Park Brake Type

Steering

Electric Power Steering (EPS), Tilt steering

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

DETAILS

Overall Length 110.0 in **Overall Width** 60.0 in

Overall Height 75.8 in

1594.2 lb* **Curb Weight**

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer, fuel

> gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

Wheel Type Alloy

Color Choices Super Black

Warranty 1 Year

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471