²⁰²³ TERYX4[™]









POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

Maximum Torque 47.0 lb-ft@ 5500 rpm

Fuel System DFI® with two 36mm Mikuni throttle bodies

Ignition TCBI with electronic advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

Ground Clearance 11.2 in

Fuel Capacity 7.9 gal

Turning Radius 16.7 ft

Cargo Bed Dimensions (LxWxH)

17.9 x 47.6 x 8.7 in

Cargo Bed Capacity 249 lb
Load Capacity 1109 lb
Seating Capacity 4

Towing Capacity 1300 lb

Lighting (2) incandescent headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / Wheel Travel

Double Wishbone; Fox Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way

compression damping/8.0 in.

Rear Suspension / Wheel Travel

Double Wishbone; Fox Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way

compression damping/8.0 in.

Front Tires Maxxis 26 x 9-12

Rear Tires Maxxis 26 x 11-12

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc

DETAILS

Frame Steel Tube Double-X Reinforcement

Overall Length 125.4 in
Overall Width 60.0 in
Overall Height 77.8 in
Curb Weight 1605.2 lb*

Wheelbase 85.6 in

Instruments Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter and parking-

brake indicator, R/N/P/4WD, water temp and low-oil-

pressure indicators

Wheel Type Steel

Color Choices Metallic Sierra Blue/Metallic Onyx Black

Warranty 1 Year



