



Mahindra

6075 Eco 2wd / 4wd

#1 TRACTOR IN THE WORLD

5 YEAR WARRANTY



Deming Prize
2003



Japan Quality Medal
2007

Mahindra
Tractors

Specifications

6075 2wd / 6075 4wd

MOTOR	
Engine	Four-Stroke, Direct Injection, Turbocharged, Water-Cooled Diesel Engine
Cylinder	4
Power (hp)	75 @ 2100
Displacement	3822 cc
EGR	-
ELECTRIC SYSTEM	
Battery	12V, 100AH
Alternator	12 V, 55 A
CLUTCH	
Type	Double Clutch
TRANSMISSION	
Type	Partial Synchronization
Number of Gears/Speeds	15 Forward, 3 Reverse
STEERING	
Type	Hydrostatic Power Steering
BRAKES	
Type	Mechanical, Oil Immersed, Multi Disc Brakes
HYDRAULIC SYSTEM	
Type	Live Hydraulics with Draft & Position Control
3-Point Linkage	Telescopic Lower Links with Cat I or II Rotating Ball Three Point Linkage and Stabilizer
Lift Capacity (lb)	4,850.17
Rear Auxiliary Remote Valves	Simple Coil
PTO	
Type	SLIPTO
PTO RPM(Engine rpm)	540
PTO hp	66
OPERATING WEIGHT	
Total (lb)	7,359.03
DIMENSION WITH AG TIRES	
Overall Length (inch)	159.37
Overall Width (inch)	78.74
TIRE SIZES AND OPTIONS	
AG (Front/Rear)	12,4 x 24 / 18,4 x 30



5 Years / 3000 Hours Warranty