



Mahindra

6075 2wd / 4wd

#1 TRACTOR IN THE WORLD

5 YEAR WARRANTY



Deming Prize
2003



Japan Quality Medal
2007

Mahindra
Tractors

Specifications

6075 2wd / 6075 4wd

ENGINE	
Type	Four Stroke, Direct Injection, Turbocharged, Water Cooled, Diesel Engine
Cylinders	4
Power (hp)	73 hp @ 1950
Displacement Cubic (cc)	3822
ELECTRICAL SYSTEM	
Battery Capacity	12 V. 100 AH
Alternator	12 V. 90 A
CLUTCH	
Type	Dual Clutch
TRANSMISSION	
Type	Partial Synchromesh With Synchro Shuttle
Number of Gears/Speeds	15 Forward, 15 Reverse
STEERING	
Type	Hydrostatic Power Steering
BRAKES	
Type	Mechanical, Oil Immersed, Multi Disc Brakes

HYDRAULIC SYSTEM	
Type	Live Hydraulics With Draft & Position Control
3-Point Linkage	Telescopic Lower Links with Cat I or II Rotating Ball Three Point Linkage and Stabilizer
Lift Capacity (kg)	5,732.02
Rear Auxiliary Remote Valves	Double Spool
PTO	
Type	SLIPTO
PTO RPM(Engine rpm)	540 @ 1950 / 540E @ 1409
PTO hp	64
OPERATION WEIGHT	
Total (lb)	7,440.60
DIMENSION WITH AG TIRES	
Overall Length (inch)	158.27
Overall Width (inch)	78.35
TIRE SIZES AND OPTIONS	
AG (Front/Rear)	11.2 x 24 / 16.9 x 30



5 Years / 3000 Hours Warranty