


Mahindra 9500 4wd

TRACTOR IN THE WORLD







Mahindra Tractors

Specifications

9500 4wd

MOTOR		
Engine	Mahindra NE 492	
Power (hp)	92	
Cylinders	4	
Intake	Turbo Charged	
Displacement	3,533 cc	
Bore and Stroke	96 x 122	
Opperating RPM	2,300	
Torque(Nm)	326 @ 1200rpm	
Air Filter	dry	
РТО		
Power (hp)	74	
Speed (rpm)	540	
Туре	Independent	
TRANSMISSION		
Туре	Syncronized	
Investor	Mechanical	
Gearbox	12 x 12	
Clutch	Dry with mechanical drive	
Differential Lock	Mechanics	
BRAKES		
Engagement	Mechanical Disk Breaks	
Туре	Oil immersed	
HYDRAULIC SYSTEM		
Hitch Type	II	
Lifting Capacity (lb)	5,511.56	
Type of Hydraulic System	Mechanical Open Center Hydraulics with Position Control	
Main Pump Flow	41.6L/Min	
Auxiliary Valves	Double	

STEERING		
Туре	Hydraulics	
ELECTRIC SYSTEM		
Battery Capacitor	12V, 88AH	
Alternator	12V, 45Amp	
CAPABILITIES		
Engine Oil (gal)	2.51	
Transmission Oil (gal)	10.57	
4WD Front Axle (gal)	1.8	
Antifreeze (gal)	2.40	
Fuel Tank (gal)	19.28	
DIMENSIONS		
Weight (lb)	7,231.16	
Total Length (inch)	161.57	
Total Width (inch)	80.71	
Total Height (inch)	99.61	
Distance Between Axis	85.79	



5 Years / 3000 Hours Warranty

